

## SM 40 T – the high-performance sliding gate operator.

### Your benefits:

- ▶ suitable for sliding gates up to 12 m width and 600 kg weight
- ▶ reliable and robust operator (IP 43) with lubricated geared motor
- ▶ control unit with various additional functions, e.g. partial opening
- ▶ connection possibilities for e.g. emergency stop, warning light, light barrier (photo cell) and safety edges

#### Single operator "SM 40 T" (item no. 5822V001)



incl. 1x sliding gate operator and  
T100 control unit

#### Complete set "SM 40 T" with one-way light barrier (item no. 3504V000)



incl. 1x sliding gate operator, T100 control unit, 4 m steel rack bonded with plastic, radio receiver (FM 868.8 MHz), 4-command transmitter (4020V000) and one-way light barrier (7020V000)

## DS 600 / DS 1200 – our strongest sliding gate operators.

### Your benefits:

- ▶ suitable for sliding gates up to 1,200 kg weight
- ▶ ideal for heavy gates, especially for industrial use
- ▶ reliable and durable operator (IP 44) with high-performance gear motor
- ▶ control unit with various additional functions, e.g. dead-man operation
- ▶ connection possibilities for e.g. emergency stop, warning light, light barrier (photo cell) and safety edges

#### "DS 600" (item no. 3408V000) for gates up to 600 kg



incl. ACM 400 S control unit

#### "DS 1200" (item no. 3409V000) for gates up to 1,200 kg



incl. ACM 400 S control unit

